

Declaration of Performance (DoP) : Nr.Gnk.06.02

| |
|--|
| <p>Stainless steel for construction purposes EU-regulation: 305/2011</p> |
|--|

Genk site / 1.4541 / Cold-rolled-work-hardened (Temper)

1.
Product-type : 1.4541
2.
Construction product : Cold-rolled-work hardened (temper) stainless steel coils,plates,sheets according to EN 10088-4
3.
Intended use: products for internal and external use for construction purposes, building constructions or civil engineering
4.
Manufacturer:

APERAM GENK
SWINNENWIJERWEG 5
3600 GENK
BELGIUM

Tel: +32 (0)89 30 21 11
E-mail: Stefaan.Maes@aperam.com
Website: <http://www.aperam.com/http://www.aperam.com/europe/news-publications/documentation/certifications/approvals>
5.
Authorised representative :Not applicable
6.
System of assessment and verification of constancy of performance : System 2+
7.
Case of the declaration of performance concerning a construction product by a harmonized standard :
TüV SÜD Industrie Service GmbH, Nr. 0036, has performed the initial inspection of the factory and factory production control and monitoring, review and approval of the factory production control according to system 2+ and issued a conformity certificate of production control :
Aperam Genk : "0036 – CPR – M – 43 – 2011"
8.
Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :
Not applicable

9.

Declared performance :

| Essential characteristics | Performance for 1.4541 | | | | Harmonised technical specification |
|------------------------------------|------------------------|-------|----------------------|-----------------|------------------------------------|
| | Finish | | | | |
| Tolerances on dimensions and shape | temper 2H | | EN ISO 9445-2 | | |
| | | | | | |
| | | | Values | | |
| | | | min(Mpa) | max(Mpa) | |
| Yield strength | temper 2H | CP350 | 350 | 500 | EN 10088-4 |
| | temper 2H | CP500 | 500 | 700 | |
| Tensile strength | temper 2H | C700 | 700 | 850 | |
| | temper 2H | C850 | 850 | 1000 | |
| Weldability | temper 2H | | chemical composition | | |
| Durability | temper 2H | | chemical composition | | |
| | | | Values | | |
| Chemical composition | temper 2H | | C ≤ 0,080 | | EN 10088-4 |
| | | | Si ≤ 1.00 | | |
| | | | Mn ≤ 2.00 | | |
| | | | P < 0,045 | | |
| | | | S ≤ 0,015 | | |
| | | | N ≤ 0,10 | | |
| | | | Cr: 17.0 - 19.0 | | |
| | | | Ni: 9.0 - 12.0 | | |
| | | | Ti: 5C - 0,70 | | |

10.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by
Joost Vantrappen - Head Customer Service
Genk, 07/02/2014

A handwritten signature in blue ink, appearing to be 'JV', enclosed in a light blue rectangular box.